

## 10. Electronic Ballasts for Compact Fluorescent Lamps - Non Dimmable

### TC PRO ELECTRONIC BALLASTS FOR COMPACT LAMPS

| IMAGE   | CATALOG NUMBER   | LAMP WATTAGES  | DIMENSIONS<br>L X W X H mm | NUMBER OF<br>TERMINALS<br>ON OUTPUT | ARTICLE<br>NUMBER | PACK<br>QTY | TRADE<br>PRICE<br>EACH |
|---|------------------|--|----------------------------|-------------------------------------|-------------------|-------------|------------------------|
|    | PC1/2X9-13TCPRO  | 1 X 9, 2 X 9<br>1 X 10, 2 X 10<br>1 X 11, 2 X 11<br>1 X 13, 2 X 13                             | 103 X 67 X 31              | 6                                   | 22176405          | 15          | \$65.80                |
|    | PC1/2X11-17TCPRO | 1 X 11, 2 X 11<br>1 X 14, 2 X 14<br>1 X 17, 2 X 17   | 103 X 67 X 31              | 6                                   | 22176406          | 15          | \$72.00                |
|    | PC1/2X18TCPRO    | 1 X 18<br>2 X 18   | 103 X 67 X 31              | 6                                   | 22176407          | 15          | \$65.80                |
|    | PC1X18/24TCLPRO  | 1 X 18 TCL<br>1 X 24 TCL   | 234 X 40 X 28              | 4                                   | 22176068          | 10          | \$65.80                |
|    | PC1/2X26-42TCPRO | 1 X 22 T5C<br>1 X 40 T5C<br>2 X 22 T5C<br>1 X 24<br>1 X 26, 2 X 26<br>1 X 32, 2 X 32<br>1 X 42 | 103 X 67 X 31              | 6                                   | 22176408          | 15          | \$72.00                |
|    | PC1X36TCLPRO     | 1 X 36 TCL<br>1 X 38 T8  | 234 X 40 X 28              | 4                                   | 22176141          | 10          | \$65.80                |
|    | PC1X40TCLPRO     | 1 X 40 TCL   | 234 X 40 X 28              | 4                                   | 22176142          | 10          | \$65.80                |
|   | PC1X55TCLPRO     | 1 X 55 TCL<br>1 X 55 T5c   | 234 X 40 X 28              | 4                                   | 22176169          | 10          | \$65.80                |
|  | PC1X57/70TCPRO   | 1 X 57<br>1 X 70   | 123 X 79 X 31              | 6                                   | 22176409          | 10          | \$65.80                |
|  | PC2X18/24TCLPRO  | 2 X 18 TCL<br>2 X 24 TCL   | 234 X 40 X 28              | 6                                   | 22176069          | 10          | \$72.00                |
|  | PC2X26-42TCPRO   | 1 X 22 + 1 X 40 T5C<br>2 X 40 T5C<br>2 X 18 TCL,<br>2 X 26<br>2 X 32, 2 X 42                   | 123 X 79 X 31              | 6                                   | 22176410          | 10          | \$72.00                |
|  | PC2X36TCLPRO     | 2 X 36 TCL<br>2 X 38 T8  | 234 X 40 X 28              | 6                                   | 22176170          | 10          | \$72.00                |
|  | PC2X40TCLPRO     | 2 X 40 TCL   | 234 X 40 X 28              | 6                                   | 22176143          | 10          | \$72.00                |
|  | PC2X55TCLPRO     | 2 X 55 TCL<br>2 X 55 T5c   | 360 X 40 X 28              | 6                                   | 22176233          | 10          | \$86.00                |

#### PRODUCT DESCRIPTION

CELMA Energy Efficiency Index A2 BAT / A2 Nominal life time up to 100,000 hours

Large temperature range Devices can operate either 1 or 2 lamps

Intelligent Voltage Guard (overvoltage indication and undervoltage shutdown)

Constant luminous flux irrespective of fluctuations in mains voltage

For luminaires of protection class 1 and protection class 2 Automatic start after replacement of defective lamps

Safety shutdown of defective lamps and at end of lamp life (EOL 2) For emergency lighting systems as per EN 50172

For luminaires with M and MM as per EN 60598, VDE 0710 and VDE 0711 Temperature protection as per EN 61347-2-3 C5e