














5. Electronic Ballasts for Linear Fluorescent Lamps - Non Dimmable

T8 PRO ELECTRONIC BALLASTS FOR LINEAR T8 LAMPS

IMAGE	CATALOG NUMBER	LAMP WATTAGES	DIMENSIONS L X W X H mm	NUMBER OF TERMINALS ON OUTPUT	ARTICLE NUMBER	PACK QTY	TRADE PRICE EACH
	PC1X18T8PRO	18	234 X 40 X 28	4	22176093	10	\$58.00
	PC1X30T8PRO	30	234 X 40 X 28	4	22176077	10	\$70.00
	PC1X36T8PRO	36	234 X 40 X 28	4	22176217	10	\$58.00
	PC1X58T8PRO	58	234 X 40 X 28	4	22176094	10	\$58.00
	PC1X70T8PRO	70	234 X 40 X 28	4	22176171	10	\$70.00
	PC2X18T8PRO	2 X 18	234 X 40 X 28	6	22176107	10	\$65.80
	PC2X30T8PRO	2 X 30	234 X 40 X 28	6	22176078	10	\$81.90
	PC2X36T8PRO	2 X 36	280 X 30 X 28	6	22185217	10	\$65.80
	PC2X58T8PRO	2 X 58	280 X 30 X 28	6	22185218	10	\$65.80
	PC2X70T8PRO	2 X 70	360 X 40 X 28	6	22176232	10	\$81.90
	PC3X18T8PRO	3 X 18	234 X 40 X 28	8	22176187	10	\$82.70
	PC4X18T8PRO	4 X 18	234 X 40 X 28	10 (2 ON INPUT END OF BALLAST)	22176163	10	\$85.50
	PC3X36T8PRO	3 X 36	360 X 40 X 28	8	22176231	10	\$82.70

PRODUCT DESCRIPTION

Average life = 50,000 hours
 Large temperature range
 Safety shutdown of defective lamps
 Automatic start after replacement of defective lamps
 For emergency lighting as per EN 50172
 Constant luminous flux irrespective of fluctuations in mains voltage
 For luminaires of protection class 1 and protection class 2
 For luminaires with F or M and MM as per EN 60598, VDE 0710 and VDE 0711
 Insulation Displacement Connection (IDC) terminal
 for rapid automatic or manual wiring
 Temperature protection as per EN 61347-2-3 C5e