








## 5. Electronic Ballasts for Linear Fluorescent Lamps - Non Dimmable

### T8 PRO ELECTRONIC BALLASTS FOR LINEAR T8 LAMPS

IMAGE	CATALOG NUMBER	LAMP WATTAGES	DIMENSIONS L X W X H mm	NUMBER OF TERMINALS ON OUTPUT	ARTICLE NUMBER	PACK QTY	TRADE PRICE EACH
	PC1X18T8PRO	1 X 18	230 X 30 X 21	4	22185213	10	\$58.00
	PC1X36T8PRO	1 X36	230 X 30 X 21	4	22185214	10	\$58.00
	PC1X58T8PRO	1 X58 T8 1 X 55 TCL	230 X 30 X 21	4	22185215	10	\$58.00
	PC2X18T8PRO	2 X 18	230 X 30 X 21	6	22185126	10	\$65.80
	PC2X36T8PRO	2 X 36	230 X 30 X 28	6	22185217	10	\$65.80
	PC2X58T8PRO	2 X 58 T8 2 X 55 TCL	230 X 30 X 28	6	22185218	10	\$65.80
	PC3/4X18T8PRO	3 X 18 4 X 18	280 X 30 X 28	8 (3X) 10* (4X) (*2 CONNECTIONS AT MAINS END)	22185219	10	\$82.70

#### PRODUCT DESCRIPTION

Average life = 50,000 hours  
 Large temperature range  
 Safety shutdown of defective lamps  
 Automatic start after replacement of defective lamps  
 For emergency lighting as per EN 50172  
 Constant luminous flux irrespective of fluctuations in mains voltage  
 For luminaires of protection class 1 and protection class 2  
 For luminaires with F or M and MM as per EN 60598, VDE 0710 and VDE 0711  
 Insulation Displacement Connection (IDC) terminal  
 for rapid automatic or manual wiring  
 Temperature protection as per EN 61347-2-3 C5e