







6. Electronic Ballasts for Linear Fluorescent Lamps - Non Dimmable

T8 TOP ELECTRONIC BALLASTS FOR LINEAR T8 LAMPS

IMAGE	CATALOG NUMBER	LAMP WATTAGES	DIMENSIONS L X W X H mm	NUMBER OF TERMINALS ON OUTPUT	ARTICLE NUMBER	PACK QTY	TRADE PRICE EACH
	PC1X18T8TOP	18	280 X 30 X 28	4	22176366	25	\$46.70
	PC1X36T8TOP	36	280 X 30 X 28	4	22176370	25	\$46.70
	PC1X58T8TOP	58	280 X 30 X 28	4	22176373	25	\$46.70
	PC2X18T8TOP	2 X 18	280 X 30 X 28	6	22176367	25	\$51.80
	PC2X36T8TOP	2 X 36	280 X 30 X 28	6	22176371	25	\$51.80
	PC2X58T8TOP	2 X 58	360 X 30 X 28	6	22176374	25	\$51.80

PRODUCT DESCRIPTION

CELMA Energy Efficiency Index A2

Nominal life time up to 50,000 hours

Large temperature range

Fixed frequency operation for constant lamp current

Lamp preheating for min. 30,000 starts without replacement of lamps

Constant luminous flux irrespective of fluctuations in mains voltage

Designed for THD < 10%

For luminaires of protection class 1 and protection class 2

Automatic start after replacement of defective lamps (detects 1 lamp)

Safety shutdown of defective lamps

Push terminal for rapid automatic or manual wiring

Temperature protection as per EN 61347-2-3 C5e